

AKWAFLEX CONTROL GEAR AND ENCLOSURES

SPECIFICATION SHEET

Project Name:

Specifier:

Location:

Product Code:



Material:
Aluminum/Stainless Steel/PC Mild Steel/
Molded Fiberglass



Impact Rating:
Varies



Weatherproof Rating:
Up to IP67/8
Wet Location



Operating Temp:
-40°F - 131°F



Lockable Options



UL Listed



Class II



Dimmable:
0-10V, DMX, Triac,
Phase Dim, DALI



REMOTE POWER SUPPLIES [PSUs]

LP040WPRITRNDIMIP	Class 2, 40W, IP67, 0-10 Dimmable Remote Constant Voltage PSU [rated for outdoor use]
LP096WPRITRNDIM	Class 2, 96W, IP67, 0-10 Dimmable Remote Constant Voltage PSU [rated for outdoor use]
LP100WPRITRNDIM	Class 2, 100W, IP64, 0-10V Dimmable Remote Constant Voltage PSU [rated for indoor use]
LPQZ96WUNV24VPH010	Class 2, 96W, IP66, Phase Dim or 0-10 Dimmable Remote Constant Voltage PSU [rated for outdoor use]
LPQZ96WUNV24VDMX1CH	Class 2, 96W, IP66, 8 Bit DMX Remote Constant Voltage PSU [rated for outdoor use]

REMOTE NEMA ENCLOSURES

LPNEMA2RENCLJR	NEMA2 INDOOR enclosure for LP100WPRITRNDIM, 12 x 3.3 x 2
LPNEMA3RENCLJR	NEMA3R Drip Proof Enclosure, 4 x 4 x 12 [IP24 Equivalent]
LPNEMA3RXENCLSS	NEMA3 304 Lockable Stainless Steel Drip Proof Enclosure 4 x 4 x 12 [IP24 Equivalent]
LPNEMA4ENCLJR	NEMA4 Watertight Enclosure, 6 x 4 x 12 [IP66 Equivalent]; NEMA4X
LPNEMA4XENCLSSJR	NEMA4 304 Lockable Stainless Steel Watertight Enclosure 6 x 4 x 12 [IP66 Equivalent] NEMA4X
LPNEMA6PTRO	NEMA6 Watertight Enclosure Wiring Trough, 2 x 3 x 14 [IP68 Equivalent]

Additional driver & enclosure configurations available, including IP68 options
Please note the KLIK UL Listing requires purchase of a remote driver and enclosure.