




Technical Specifications - D Series

D

“W” configuration - Flush fitting cover fastened by captive lid screws.



W Construction

Material	Hot compression molded fiberglass reinforced polyester (thermoset)
Gasket	Poured polyurethane seamless gasket provides watertight, dust-tight environmental seal
Recessed Screws	No protruding surfaces
Stainless Steel Hardware	300 Series stainless used on all hardware
Mounting Bosses	Panel mounting capability for fixed rear panel
Metal inserts	All bosses utilize threaded brass inserts accepting 10-32 screws
Soft Edge Design	Rounded edges, minimal protrusions or exposed pocket areas for assembly of dust and debris

W Industry Standards

UL/cUL 50/508	File E64358 Type 1, 3, 3S, 4X, 6, 6P, 12
NEMA 250	Type 1, 3, 3S, 4X, 6, 6P, 12
CSA Std C22.2	File LR069014 Type 1, 3, 3S, 4X, 6, 6P, 12
IEC 529	IP66, IP67, IP68
Temperature Range	(-26°F to +257°F) (-32°C to +125°C)
Flammability Rating	UL94-V0
Self Extinguishing	Non-halogenated, Non-flame propagating

W Accessories

Back Panels

Carbon Steel	BP__CS	pg. 153
---------------------	--------	---------

Accessories

Drain & Breather Vents	pg. 144, 146
Hole Plugs	pg. 145
Assorted Hubs and Cord Grips	pg. 145, 148
All Other Accessories	pg. 144 - 159

W Modifications

Custom Colors	pg. 12 - 13
Silk Screening	pg. 12 - 13
EMI/RFI Shielding	pg. 12 - 13
Custom Window	pg. 12 - 13
Custom Cutouts/Holes	pg. 12 - 13

Product Detail

