



### KLIKLED® KLIK LEDpod™

| Optics                |     |      | Lens          |     |     |     |     |
|-----------------------|-----|------|---------------|-----|-----|-----|-----|
| Beam Angle            |     |      | NSP           | SP  | NFL | FL  | SPR |
| LOR defined by optics |     |      | 80            | 84  | 82  | 85  | 76  |
| lm                    | W   | mA   | System Lumens |     |     |     |     |
| 179                   | 2.3 | 350  | 144           | 151 | 147 | 153 | 137 |
| 243                   | 3.2 | 500  | 195           | 205 | 200 | 207 | 185 |
| 320                   | 4.5 | 700  | 256           | 269 | 263 | 272 | 244 |
| 422                   | 6.6 | 1000 | 338           | 355 | 347 | 359 | 321 |

NSP - narrow spot 10-19° · SP - spot 20-34° · NFL - narrow flood 35-49° · FL - flood 50-69° · SPR - spreader 20x60°

|                           |   |
|---------------------------|---|
| <b>Color</b>              | 3000K · 4000K · 5000K · Red · Green · Blue · Amber · RGBW |
| <b>CRI</b>                | 80-85   |
| <b>Binning</b>            | 2 McAdam Step   |
| <b>Driver - Primary</b>   | 110 - 277 VAC UL Listed Constant Voltage                  |
| <b>Driver - Secondary</b> | 350 - 1000mA Constant Current                             |
| <b>Control</b>            | DALI · 0-10V · DMX*                                       |
| <b>Distribution</b>       | Symmetrical · Spreader                                    |
| <b>Tube Size</b>          | RHS min 2.5" height, Max. wall .25" †                     |
| <b>Cut Out</b>            | 1.3125"   |
| <b>Weight</b>             | 0.19 LBS  |

All IP rated luminaires tested to AS60529-2004 Degrees of protection provided by enclosures (IP Code)

\* DMX control is for overall dimming only and not for individually addressed LEDpod

† Others sizes available upon request

#### primary driver



110 - 277 primary voltage

10" x 1.5" x 2"

remotely mounted

dimming control