



MISTIK028 REC SPEC SHEET



POST DIAMETER
Ø38 · Ø42 · Ø48

38 SQ



Optics			Reflector	
Beam Angle			symmetrical	asymmetrical
lm	W	mA	System Lumens ¹	
165	1.4	350	126	123
235	2	500	179	174
284	2.5	700	216	211
Colour	2200K · 2700K · 3000K · 4000K · 5000K · Red · Green · Blue · Amber · PC Amber			
CRI	80-85			
Binning	2 McAdam Step			
Driver	Output 350 - 700mA Constant Current (Provided with fixture based on selected wattage; Compatible with KLIK 24VDC power supply)			
Control	0-10V · DMX* · DALI			
Mounting	By others · 0.26in hole provided top and bottom for surface mounting			
Distribution	symmetric · asymmetric · soft symmetric · soft asymmetric · frost symmetric · frost asymmetric			
Weight	0.1lbs			

* DMX control is for overall dimming only and not for individually addressed LEDpods
1 Lumen output based on 4000K

MTK028KAPSD 20200904

Product Codes

Follow the steps to specify your fixture. Enter Product Code in field at top of page. Example: **LPMISTIK028CYL30KA2.0WFLD**

Fixture Type	Color ¹	Distribution	Wattage	Lens ^{2,4}	Mounting	Custom Bezel ^{3,4,5}
LPMISTIK028 REC	2&K 3000K	A Asymmetric S Symmetric	1.4W 1.4 Watts	FLD Clear Flood (Standard)	FLT Flat Surface P38 1.5" OD post P42 1.66" OD post P48 1.90" OD post	RAL Custom Powdercoat, Specify RAL#
	27K 2700K		2.0W 2.0 Watts	FRS Frosted		
	30K 3000K	2.5W 2.5 Watts	SFT Light Filter			
	35K 3500K					
	40K 4000K					
	50K 5000K					
AMB Amber						
PCA Phosphor-Converted Amber						

1. Other colors on request.
2. Clear FLD (Flood lens standard; FRS is heavy opaque; SFT is light filter).
3. Specify RAL#
4. **Additional charges and lead time apply for this feature.**
5. Colored anodized bezel available, contact factory

