


MISTIK028 REC **SPEC**SHEET



POST DIAMETER
 Ø38 · Ø42 · Ø48



Project Name: _____

Specifier: _____

Location: _____

Product Code: _____

Optics			Reflector	
Beam Angle			symmetrical	asymmetrical
lm	W	mA	System Lumens ¹	
165	1.4	350	126	123
235	2	500	179	174
284	2.5	700	216	211
Colour	2200K · 2700K · 3000K · 4000K · 5000K · Red · Green · Blue · Amber · PC Amber			
CRI	80-85			
Binning	2 McAdam Step			
Driver	Output 350 - 700mA Constant Current (Provided with fixture based on selected wattage; Compatible with KLIK 24VDC power supply)			
Control	0-10V · DMX* · DALI			
Mounting	By others · 0.26in hole provided top and bottom for surface mounting			
Distribution	symmetric · asymmetric · soft symmetric · soft asymmetric · frost symmetric · frost asymmetric			
Weight	0.1lbs			

* DMX control is for overall dimming only and not for individually addressed LEDpods
 1 Lumen output based on 4000K

MTK028KAPSD 20200904

Product Codes

Follow the steps to specify your fixture. Enter Product Code in field at top of page. Example: **LPMISTIK028CYL30KA2.0WFLD**

Fixture Type	Color ¹	Distribution	Wattage	Lens ^{2,4}	Mounting	Custom Bezel ^{3,4,5}
LPMISTIK028 CYL	2&K 3000K	A Asymmetric S Symmetric	1.4W 1.4 Watts	FLD Clear Flood (Standard) FRS Frosted SFT Light Filter	FLT Flat Surface P38 1.5" OD post P42 1.66" OD post P48 1.90" OD post	RAL Custom Powdercoat, Specify RAL#
	27K 2700K		2.0W 2.0 Watts			
	30K 3000K	2.5W 2.5 Watts				
	35K 3500K					
	40K 4000K					
	50K 5000K					
	AMB Amber					
PCA Phosphor-Converted Amber						

1. Other colors on request.
2. Clear FLD (Flood lens standard; FRS is heavy opaque; SFT is light filter).
3. Specify RAL#
4. **Additional charges and lead time apply for this feature.**
5. Colored anodized bezel available, contact factory

