



0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100



# LEDSTREAM ECO 37 Recessed 13 MM Gyprock Installation Instructions


Patented

Revised 10.27.2016




1.

Determine position of fitting, cut out slot for lamp unit. Connect 24V wiring and push into place.



Cut out size calculation.



2.

Installed.

## Important


Fixing Surface must be flat and free of any distortion.

Maximum distance between fixings is 900mm and 100mm from the ends or corners.

Using appropriate fasteners to suit the mounting surface is the responsibility of the installer.

[www.klikusa.com](http://www.klikusa.com)


[sales@klikusa.com](mailto:sales@klikusa.com)




# LEDSTREAM ECO 37 Recessed 38 MM Deep Slot Installation Instructions

Patented


Revised 10.27.2016




Cut out size calculation.



Determine position of fitting, prepare 16mm deep slot for lamp unit. Drill 16mmØ hole for wiring at end of slot.



Connect 24V wiring and push lamp unit into place.



Installed.

## Important

Fixing Surface must be flat and free of any distortion.


Maximum distance between fixings is 900mm and 100mm from the ends or corners.

Using appropriate fasteners to suit the mounting surface is the responsibility of the installer.

[www.klikusa.com](http://www.klikusa.com)

[sales@klikusa.com](mailto:sales@klikusa.com)


Page: 1 of 1 - 10780-06-A



# LEDstream ECO 37 Recessed Lanyard Instruction

Patented

Revised 10.27.2016



Item #	Title
1	Suspension Ceiling Barrel
2	Suspension Ceiling Barrel Cap
3	Gripper Wire 0.5m
4	Gripper Sling A
5	Gripper Sling B
6	Suspension Sling
7	Ledstream ECO 37 REC
8	Fastener

## Ledstream Recess ECO 37 Lanyard Instruction


Step 1: Remove gripper wire (3) from Gripper sling (5).

Step 2: Install Suspension ceiling barrel (1) inside ceiling void.

Step 3: Re-install Gripper wire (3).

Step 4: Use lanyards to suspend Ledstream ECO 37 Recess under ceiling.

Step 5: Install as per ECO 37 instruction sheet.



## Important

- Using appropriate fasteners to suit the mounting surface is the responsibility of the installer.

- Units should be evenly suspended to avoid the over-loading of suspension wires.

- A maximum loading of 50kg is recommended on a single wire at any one time.

Please ensure that excess suspension wire cannot contact live wires by either

a) insulating excess wire

b) cut off excess wire (if wire is cut, the fitting cannot be removed and refitted unless new suspension wire is used)

c) If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or similar qualified person in order to avoid a hazard

